

CIRCULATING OILS

Application: lubricating oil for plain and roller bearings, vacuum pumps, gearboxes, circulation systems, etc. where (non-EP) zinc-free additive pack in mineral oil is recommended and approved.

Characteristics High quality multi purpose oils made from highly refined paraffinic base oils. These oils are blended to prevent corrosion, increased oxidation stability and decrease in sludge.

These oils release water and air quick and completely. They also have a naturally high viscosity index (VI), the viscosity / temperature characteristics are excellent.

The wear reducing performance is especially good and the pour points are in comparison to the ISO Grade are very low.

These oils are compatible with all mineral oil resistant seal materials.

Specification:

Viscosity GRADE (ISO3448)	Density At 15°C (IP365)	Viscosity At 40°C mm ² /s (IP71)	Viscosity At 50°C mm ² /s	Viscosity At 100°C mm ² /s (IP71)	Viscosity INDEX (IP226)	Flash Point °C	Pour Point °C
10	0.856	10	6	2.5	105	190	-6
22	0.862	22	15	4.3	105	195	-33
32	0.870	32	21	5.3	105	205	-33
46	0.876	46	30	6.7	105	230	-33
68	0.880	68	43	8.8	105	240	-30
100	0.888	100	60	11.0	100	250	-27
150	0.890	150	87	14.5	100	260	-24
220	0.895	220	125	19	100	270	-21
320	0.898	320	180	24	100	280	-18
460	0.9	460	257	38	100	280	-16