

TRUE LUBRICANTS

COMPRESSOR "S" OIL

MEETS : DIN 51506 VD-L

Applications:

COMP S OIL is a range of highly refined mineral compressor oils. Fortified with special "S" additives to enhance performance. Specially designed for reciprocating, screw and rotary-vane compressors and turbines.

COMP S oils , have the following advantages:

- High oxidation and corrosion resistance.
- Very little evaporation.
- Excellent temperature stability, with high viscosity Index
- **Reduced** carbon deposits.
- Better heat distribution.
- Excellent lubricity.
- Less wear.
- Use less energy, savings of up to 15 %.
- Longer drain intervals.
- Compatible with mineral oils.
- Environmental friendly.
- Quick air separation.
- Very good demulsibility.
- Extends drain intervals

Specification:

DIN 51506 ; DIN VBL , VC/VC-L , VD-L

Data:

ISO GRADES	32	46	68	100	150
Density @ 20°C	0.880	0.881	0.886	0.889	0.960
Viscosity @ 40°C	32	46	68	90	150
Viscosity @ 100 °C	5.9	7.6	10.2	12.8	14.8
Viscosity index	137	140	143	145	145
Pour Point °C	-52	-49	-47	-48	-45
Flash Point °C	240	250	255	300	300

Toxicity:

Toxic class: Free.

Disposal:

Transport:

Not dangerous goods.

Special note:

Please check the Manufacture's Manual for the oil grade.