

## HD SAE 30

**Application areas:** **MOTOR TURBO HD SAE 30** is a mono-grade HD motor oil for Diesel and Petrol motors. Including hard working turbo-charged and naturally aspirated diesel engines. It can also be used for the lubrication of piston compressors and as hydraulic oil in accordance with the manufacturers protocol.

**Characteristics:** **MOTOR TURBO HD SAE 30** offers full lubrication even at high temperatures. It also offers very good wear protection. Excellent cleanliness of motor (reduces the formation of the sludge).

- Full lubrication ability even at high temperatures.
- Optimal wear protection
- Excellent cleanliness of motor (no sludge)
- It is suitable for catalysts
- Very good protection on wear on the Bore.

### **Specifications & Approvals:**

- ACEA E2	- MB 227.0
- API : SL / CF 4	- MIL-L-2104 D
- MAN 270	- MIL-L-46152 B
- VOLVO VDS	- CCMC D2/G2
- CATERPILLAR TO-2	- MACK EO
- ALISON C-4	

### **Data:**

Density at 20°C g/cm <sup>3</sup>	0,87
Pour point °C	-30
TBN mg KOH/g	11
Sulphated Ash %	1,3
SAE Class availability	30
Viscosity @ 100°C	9 cSt – 12cSt

**Transport:** ADR/SDR Not dangerous goods

**Disposal:** VVS-Code

**Toxicity:** Toxic Class Free  
BAG T Nr 617 200