
TRUE HYDRAULIC OIL HD 32 / 46 / 68 / 100

Zinc Type Anti-Wear Hydraulic Fluid

Description

TRUE HYDRAULIC OIL is a range of premium quality anti-wear hydraulic oils. They are blended from virgin paraffinic base oils. They contain anti-wear, anti-rust, anti-oxidant and anti-foam additives to give excellent performance and wear protection. They are recommended for use in any circulating hydraulic system where a zinc containing anti-wear hydraulic oil is called for.

Performance Benefits

HYDRAULIC OILS have the following features:

- Good corrosion protection
- Effective anti-wear properties
- Long equipment life
- Excellent oxidation resistance

Specifications:

- Good corrosion protection
- Effective anti-wear properties
- Long equipment life

Directions for Use

HYDRAULIC OILS may be used in any circulating hydraulic system, which calls for the use of anti-wear hydraulic oil containing a zinc anti-wear additive. They are also suitable for use in machine tools such as the headstocks of lathes, which specify the use of hydraulic oil. They should not be used in a system which contains silver plated components.

Technical Data

ISO grade	32	46	68	100
Viscosity @ 40°C	32	46	68	100
Viscosity @ 100°C	5.1	6.5	8.5	10
Viscosity Index	97	96	95	95
Flash Point °C	200	210	220	220
Pour Point °C	-30	-30	-30	-28

Pack Sizes

210 Lts Drum
20 Lts Pail
5 Lts Bottle